

New Model Information

New for 2009!



NSF 15/20C

Power Tilt

- ✓ The perfect choice for inflatable, small fishing boats and pontoon boats.
- ✓ Available in shaft lengths including 15 and 20 inches, for multiple applications.
- ✓ Light and compact power tilt and transom bracket.
- ✓ Power tilt system for greater operating convenience.
- ✓ Ultra-low emissions, exceed EPA and CARB emission standards.



* Tiller handle model available in spring 2009.

Features

Manual starter with auto decompression



Light and compact power tilt and transom bracket.



Overhead cam provides smooth, quiet and efficient operation

Buckle-type cowl latch

Unique engine mount system reduces vibration

Dual water pickups in gearcase

Specifications

Model	NSF15C EPT	NSF20C EPT
Engine (No. of Cylinder)	2	2
Engine Type	4 Stroke	4 Stroke
Output	15 hp (11 kw)	20 hp (14.7 kw)
Displacement	351 cc (21.42 cu.in.)	351 cc (21.42 cu.in.)
Bore x Stroke	61 x 60 mm (2.4 x 2.36 in)	61 x 60 mm (2.4 x 2.36 in)
Valve System	SOHC 2-valves per cyl	SOHC 2-valves per cyl
Starting	Electric (with manual starter)	Electric (with manual starter)
Control Type	Remote Control	Remote Control
Gear Ratio	13:28	13:28
Propeller	3 Blade Aluminum STD	3 Blade Aluminum STD
Transom Height	15", 20"	15", 20"
Fuel	Unleaded Gasoline (87 Octane)	Unleaded Gasoline (87 Octane)
Oil Type	SAE 10W-30/40 (SF,SG,SH,SJ,SL,SM)	SAE 10W-30/40 (SF,SG,SH,SJ,SL,SM)
Fuel Tank	25 Lit (6 US gal) Separate Tank	25 Lit (6 US gal) Separate Tank
Weight	15": 61 kg (134 lbs) 20": 62.5 kg (138 lbs) 25": 64kg (141 lbs)	15": 61 kg (134 lbs) 20": 62.5 kg (138 lbs)
Alternator Output	Standard: 12V 145W, 11A	Standard: 12V 145W, 11A
Max. RPM Range	5,000-6,000	5,400-6,100